

Cross Cylindrical Roller Slewing Bearing with Internal Gear

No.	Boundary Dimension			Bearing Type	Related Dimension											Gear Parameter					Weight kg ≈	
	d	D	T		D1	d1	d2	Dwp	H	h	n1	n2	n3	φ 1	φ 2	φ 3	da	b	m	Z		x
1	695	920	90	2797/695G2	870	735	800	802	76	4	3	30	30	10	18	18	658	65	7	96	0	175
2	760	1000	95	2797/760G2	956	800	878	880	82	15	4	24	24	M10×1	20	20	718.18	70	8	91	0.35	206
3	870	1180	115	2797/870G2	1125	920	1023	1025	100	15	2	18	18	M8×1	26	26	828.8	90	8	105	0.3	374
4	875	1170	95	2797/875G2	1120	930	1018	1020	82	15	4	24	24	M10×1	22	22	830.1	70	8	105	0.35	297
5	955	1200	90	2797/955G	1160	1000	1088	1090	76	14	4	18	36	M8×1	18	18	908.8	72	8	115	0.3	245
6	955	1200	90	2797/955G2	1160	1000	1088	1090	76	14	4	18	36	M8×1	18	18	908.8	72	8	115	0.3	245
7	1010	1200	90	2797/1010G2	1160	1041	1088	1090	76	10	2	20	36	M8×1	M20	22	962	72	10	97	0.6	199
8	1010	1200	90	2797/1010GK	1160	1041	1088	1090	76	10	2	20	36	M8×1	M20	22	962	72	10	97	0.6	199
9	—	1216	100	113.28.1094.03	1172	1013	1092	1094	90	10	4	12	12	M10×1	M18	22	920	90	10	94	0	326
10	1278	1595	120	2797/1278G2	1535	1335	1428	1430	106	14	6	36	36	M10×1	26	26	1221.14	90	12	103	0.35	585
11	1400	1715	110	2792/1400G2K	1660	1460	1558	1560	95	15	4	40	40	M10×1	M24	26	1330	90	10	135	0	587
12	1424	1776	160	113.40.1600.03 K	1724	1476	1598.5	1600	150	39	5	45	45	M10×1	26	26	1349.6	90	14	97	0.5	924
13	1665	2002	156	113.45.1830.11	1940	1720	1827	1830	128	28	6	54	54	M10×1	30	30	1610	100	12	135	0.5	912
14	2100	2335	160	2792/2000G2	2350	2070	2207	2210	140	20	6	48	48	M10×1	M30	33	1913.5	120	14	138	0.3	1607
15	2032	2335	124	2797/2032	2280	2144	2206	2208	80	20	6	64	64	M10×1	M20	22	2032	100	14	147	0	630
16	2240	2670	160	2792/2240G	2600	2320	2457	2460	140	20	6	54	54	M12×1.25	M36	35	2154.5	120	16	136	0.3	1798
17	2300	2800	208	3-940G	2710	2390	2535	2540	180	18	6	48	42	M10×1	M36	38	2162.75	175	20	110	0	2756
18	2325	2678	162	D2797/2325	2610	2391	2498	2500	145	17	8	56	56	M10×1	33	33	2234.4	110	12	188	0	1627
19	2680	3325	300	2797/2680GY	3242	2754	2996	2998.48	270	30	4	48	48	M16×1.5	33	33	2592	180	16	164	0	6320
20	2680	3325	300	2797/2680GK	3242	2754	2996	2998.48	270	30	4	32	32	M16×1.5	33	33	2592	180	16	164	0	6641
21	2680	3325	300	2797/2680G	3242	2754	2996	2998.48	270	30	4	32	32	M16×1.5	33	33	2592	180	16	164	0	6320
22	—	3100	110	2797/2768	3052	2897	2972	2974.5	94	16	10	60	60	M10	24	24	2768	100	16	175	0	975
23	3322	3850	200	3-943G2	3720	3420	3568	3570	180	22	12	60	60	Z1/4	45	45	3206.368	158	22	147	0.35	4520
24	3780	4500	260	2797/3780G2	4400	3900	4055	4150	238	32	12	64	60	M16×1.5	40	40	3668.24	190	22	168	0.35	8346